

Product Specifications For 262D3



Operating Specifications

Rated Operating Capacity	2700 lb
---------------------------------	---------

Rated Operating Capacity with Optional Counterweight	3055 lb
---	---------

Tipping Load	5400 lb
---------------------	---------

Breakout Force - Tilt Cylinder	7355 lb
---------------------------------------	---------

Note Operating Weight, Operating Specifications and Dimensions all based on 75 kg (165 lb) operator, all fluids, one speed, OROPS, 1730 mm (68 in) low profile bucket, Cat PC 12 × 16.5 tires, standard flow hydraulics, mechanical suspension seat, no optional counterweights and manual quick coupler (unless otherwise noted).

Weights

Operating Weight	8296 lb
-------------------------	---------

Note Operating Weight, Operating Specifications and Dimensions all based on 75 kg (165 lb) operator, all fluids, one speed, OROPS, 1730 mm (68 in) low profile bucket, Cat PC 12 × 16.5 tires, standard flow hydraulics, mechanical suspension seat, no optional counterweights and manual quick coupler (unless otherwise noted).

Dimensions

Wheel Base	49.2 in
-------------------	---------

Length - With Bucket on Ground	146.2 in
---------------------------------------	----------

Length - Without Bucket	117.9 in
--------------------------------	----------

Height - Top of Cab	83.1 in
----------------------------	---------

**Vehicle Width over
Tires** 66 in

**Maximum Overall
Height** 157.8 in

**Bucket Pin Height -
Maximum Lift** 124.9 in

**Bucket Pin Height -
Carry Position** 7.9 in

**Reach - Maximum
Lift/Dump** 30.9 in

**Clearance at
Maximum Lift and
Dump** 93.7 in

Ground Clearance 8.9 ft

Departure Angle 26°

**Bumper Overhang -
Rear Axle** 42.6 in

Maximum Dump Angle 51°

**Rack Back Angle -
Maximum Height** 84°

**Bucket Pin Reach -
Maximum Lift** 15.5 in

**Turning Radius from
Center - Bucket** 85.9 in

**Turning Radius from
Center - Coupler** 55.2 in

Note Operating Weight, Operating Specifications and Dimensions all based on 75 kg (165 lb) operator, all fluids, one speed, OROPS, 1730 mm (68 in) low profile bucket, Cat PC 12 × 16.5 tires, standard flow hydraulics, mechanical suspension seat, no optional counterweights and manual quick coupler (unless otherwise noted).

**Maximum Reach -
With Arms Parallel to
Ground** 50.9 in

**Turning Radius from
Center - Machine Rear** 71.1 in

Hydraulic System

Hydraulic Flow - High Flow XPS - Maximum Loader Hydraulic Pressure 4061 psi

Hydraulic Flow - High Flow XPS - Hydraulic Power (Calculated) 76 HP

Hydraulic Flow - Standard - Hydraulic Power (Calculated) 44 HP

Hydraulic Flow - Standard - Loader Hydraulic Pressure 3335 psi

Hydraulic Flow - Standard - Loader Hydraulic Flow 23 gal/min

Hydraulic Flow - High Flow XPS - Maximum Loader Hydraulic Flow 32 gal/min

Cab

ROPS ISO 3471:2008

FOPS ISO 3449:2005 Level I

Power Train

Travel Speed - Forward or Reverse - Two Speed Option 11 mile/h

Travel Speed - Forward or Reverse - One Speed 7.7 mile/h

Service Refill Capacities

Chain Box - Each Side	3.3 gal (US)
------------------------------	--------------

Cooling System	3.7 gal (US)
-----------------------	--------------

Engine Crankcase	3 gal (US)
-------------------------	------------

Hydraulic System	13.7 gal (US)
-------------------------	---------------

Hydraulic Tank	10.3 gal (US)
-----------------------	---------------

Engine

Net Power - SAE 1349	72.9 HP
-----------------------------	---------

Displacement	203 in ³
---------------------	---------------------

Stroke	4.7 in
---------------	--------

Bore	3.7 in
-------------	--------

Peak Torque - 1,500 rpm - SAE J1995	195 ft·lbf
--	------------

Net Power - ISO 9249	73.7 HP
-----------------------------	---------

Engine Model	Cat C3.3B DIT (turbo)
---------------------	-----------------------

Noise Level

Note (1)	Cab and Rollover Protective Structures (ROPS) are standard in North America and Europe.
-----------------	---

Inside Cab*	81 dB(A)
--------------------	----------

Note (2)	*The declared dynamic operator sound pressure levels per ISO 6396:2008. The measurements were conducted with the cab doors and windows closed and at 70% of the maximum engine cooling fan speed. The sound level may vary at different engine cooling fan speeds.
-----------------	--

Outside Cab**	101 dB(A)
----------------------	-----------

Note (3)

**The labeled sound power level for the CE marked configurations when measured according to the test procedure and conditions specified in 2000/14/EC.

Air Conditioning System (If Equipped)

Air Conditioning

The air conditioning system on this machine contains the fluorinated greenhouse gas refrigerant R134a (Global Warming Potential = 1430). The system contains 1 kg of refrigerant which has a CO2 equivalent of 1.430 metric tonnes.

262D3 Standard Equipment

ELECTRICAL

12 volt Electrical System

80 ampere Alternator

Ignition Key Start/Stop Switch

Lights: Gauge Backlighting, Two Rear Tail Lights, Two Rear Halogen Working Lights, Two Adjustable Front Halogen Lights, Dome Light

Backup Alarm

Heavy Duty Battery, 850 CCA

OPERATOR ENVIRONMENT

Advanced Display with Rearview Camera: Full Color, 127 mm (5 in) LCD screen; Advanced Multi-operator Security System; On-screen Adjustments for Implement Response, Hystat Response and Creep Control

Gauges: Fuel Level, Hour Meter

Operator Warning System Indicators: Air Filter Restriction, Alternator Output, Armrest Raised/Operator Out of Seat, Engine Coolant Temperature, Engine Oil Pressure, Glow Plug Activation, Hydraulic Filter Restriction, Hydraulic Oil Temperature, Park Brake Engaged, Engine Emission System

Adjustable Vinyl Seat

Fold In Ergonomic Contoured Armrest

Control Interlock System, when operator leaves seat or armrest raised: Hydraulic System Disables, Hydrostatic Transmission Disables, Parking Brake Engages

ROPS Cab, Open, Tilt Up

FOPS, Level I

Top and Rear Windows

Floor Mat

Interior Rearview Mirror

12 volt Electric Socket

Horn

Hand (Dial) Throttle, Electronic

Adjustable Joystick Controls

Anti-theft Security System with 6-button Keypad

Storage Compartment with Netting

POWER TRAIN

Cat C3.3B, Turbo Diesel Engine, Meeting Tier 4 Final and Stage V Emission Standards

Air Cleaner, Dual Element, Radial Seal
S·O·SSM Sampling Valve, Hydraulic Oil
Filters, Cartridge-type, Hydraulic
Filters, Canister-type, Fuel and Water Separator
Radiator/Hydraulic Oil Cooler (side-by-side)
Spring Applied, Hydraulically Released Parking Brakes
Hydrostatic Transmission
Four Wheel Chain Drive

OTHER

Engine Enclosure, Lockable
Extended Life Antifreeze, -37° C (-34° F)
Machine Tie Down Points (6)
Support, Lift Arm
Hydraulic Oil Level Sight Gauge
Radiator Coolant Level Sight Gauge
Radiator, Expansion Bottle
Cat ToughGuard™ Hose
Auxiliary, Hydraulics, Continuous Flow
Heavy Duty, Flat Faced Quick Disconnects with Integrated Pressure Release
Split D-Ring to Route Work Tool Hoses Along Side of Left Lift Arm
Electrical Outlet, Beacon
Belly Pan Cleanout
Variable Speed Demand Fan
Product Link™ PL240, Cellular

MANDATORY EQUIPMENT

Hydraulics, Standard or High Flow XPS
Quick Coupler, Mechanical or Powered
High Visibility Seat Belt, 50 mm (2 in) or 75 mm (3 in)
Power Train: One Speed, One Speed with Ride Control, Two Speed or Two Speed with Ride Control
PERFORMANCE PACKAGES:

- Performance Package H1: Standard Flow Hydraulics (No Self Level)
- Performance Package H2: Standard Flow, Dual Direction Electronic Self Level (Raise and Lower), Work Tool Return to Dig, Work Tool Positioner, and Electronic Snubbing (Raise and Lower)
- Performance Package H3: High Flow XPS, Dual Direction Electronic Self Level (Raise and Lower), Work Tool Return to Dig, Work Tool Positioner, and Electronic Snubbing (Raise and Lower)

COMFORT PACKAGES:

- Open ROPS (C0): Static Seat (No Foot Throttle, Headliner, Heater or Door)
- Open ROPS (C1): Foot Throttle, Headliner, Cup Holder, and choice of Seat (Mechanical Suspension or High Back, Heated, Air Ride Seat) (No Heater or Door)
- Enclosed ROPS with Heater (C2): Foot Throttle, Headliner, Heater and Defroster, Side Windows, Cup Holder, Radio Ready, choice of Seat (Mechanical Suspension or High Back, Heated, Air Ride Seat) and Door (Glass or Polycarbonate)
- Enclosed ROPS with A/C (C3): C2 + Air Conditioner

262D3 Optional Equipment

OPTIONAL EQUIPMENT

Hand-Foot Style Controls

External Counterweights

Beacon, Rotating

Engine Block Heater - 120V

Oil, Hydraulic, Cold Operation

Paint, Custom

Heavy Duty Battery, 1,000 CCA

Product Link PL641, Cellular

Bluetooth® Radio with Microphone (AM/FM/Weather Band Receiver with USB and Auxiliary Input Jack)