

PREMIER Equipment

Farm Family Owned Since 1951

P.O. Box 355
ISABEL, SD 57633
Ph: 605.466.2119
Fax: 605.466.2107

1801 E. GRAND CROSSING
MOBRIDGE, SD 57601
Ph: 605.845.5400
Fax: 605.845.5402

13045 SD Hwy 34
STURGIS, SD 57785
Phone: 605-347-4493
Fax: 605-347-4494

P.O. Box 560
BOWDLE, SD 57428
Ph: 605.285.6133
Fax: 605.285-6498

2025 US Hwy 14 W
HURON, SD 57350
Ph: 605.352.7100
Fax: 605.352.7071

PO Box 596
EUREKA, SD 57437
Ph: 605.284.2767
Fax: 605.284.2001

Name of Purchaser Jerry L. Minchow Date 9-25-, 2023

Address 8181 Davey RD Lincoln NE 68517 New Used As Follows:

Make	Model	Color	Type	Year
Engine No	Serial No. <u>2A2177BCOK0013114</u>		<u>I14659</u>	

Agre



De

Credits

Contract to be paid to _____ In _____ Installments of \$ _____ and
One Installment of \$ _____ First Installment Due _____

This order comprises the entire agreement affecting this purchase and no other agreement or understanding of any nature concerning same has been made or entered into or will be recognized. I hereby certify that no credit has been extended to me for the purchase of this motor vehicle except as appears in writing on the face of this agreement. I further certify that I am 21 years of age or older, and hereby acknowledge receipt of a copy of this order. I FURTHER CERTIFY THAT THE ABOVE PROPERTY IS NOT SUBJECT TO ANY MORTGAGES OR LIENS EXCEPT AS FOLLOWS:

Signed Jerry L. Minchow Purchaser

Address _____

Res. Phone: _____ Bus. Phone: _____

Chakr Shetty
Salesman

440-450-650-660-670-680 PRO-DRIVE / 450-670 VT-DRIVE

X7

MCCORMICK

X7.680
POWER PLUS

MCCORMICK

X7 Models with Pro-Drive Transmission

Tractor Model		X7.440	X7.450	X7.650	X7.660	X7.670	X7.680	
Configurations Available		Standard & Premium	Premium only	Standard only	Standard & Premium	Premium only	Premium only	
Performance								
Rated ISO Engine HP @ 2200 RPM	HP (kW)	135 (99)	152 (112)	152 (112)	159 (117)	166 (122)	181 (133)	
Rated ISO PTO HP @ 2200 RPM*	HP (kW)	108 (80)	124 (92)	124 (92)	131 (98)	140 (103)	150 (110)	
Max. ISO Engine HP @ 1900 RPM	HP (kW)	143 (105)	160 (118)	160 (118)	175 (129)**	192 (141)**	212 (156)**	
Max. ISO PTO HP @ 1900 RPM*	HP (kW)	115 (86)	132 (98)	132 (98)	147 (109)**	157 (117)**	181 (135)**	
Max. Engine Torque @ 1400 RPM	lb ft (Nm)	435 (590)	499 (676)	499 (676)	535 (726)**	597 (810)**	639 (867)**	
Torque Rise		41%	41%	41%	41%	41%	37%	
Engine								
Engine Type	BETAPOWER diesel engine; Tier 4 using advanced Selective Catalytic Reduction (SCR) technology							
Engine Size	4.5 Liter, 4-cylinder			6.7 Liter, 6-cylinder				
Fuel / DEF Capacity	gal (liter)	74 (280) / 10 (38)			85 (320) / 10 (38)			
Drive Train								
Transmission Type	'Pro-Drive' 24 x 24 power shift and power shuttle; standard 8:1 creeper; 32 mph (50 kph) capable							
Gears and Ranges	4 gears and 6 ranges; fully automated shifting via push button							
Rear Axle	Internal planetary final drives; wet disc brakes; flange with bar axle adaptors							
Differential Lock	Front and rear fully locking differentials; electronic control; hydraulic engagement							
4wd Front Axle	Push button engagement, center locking differential; outboard planetary final drives; 4-wheel braking; available suspension							
Hydraulics, 3-point Hitch, PTO								
Implement Hydraulic System Type/Max. Flow	gpm (lpm)	Closed Center PFC with dedicated variable piston pump / 32.5 (123)						
Rear Remote Valves		3 standard; up to 5 available			4 standard; up to 5 available			
Rear 3-point Hitch Type		Category 3 / 3N (narrow); electronic control				Category 3; electronic control		
Rear 3-point Lift Capacity @ Hitch	lb (kg)	14,000 (6300) on Standard models; 20,500 (9300) on Premium models				20,500 (9300)		
Rear PTO		540 / 540E / 1000 / 1000E standard; electro-hydraulic engagement; rear fender controls						
Operator's Area								
Cab	Large 4-post structure; 2 doors; flat foot deck; high capacity HVAC; roofline window; available suspension							
Seat and Front Dash	Deluxe air suspended seat; tilt and telescopic steering wheel; hide-away instructor's seat; front dash with user interface							
Wheelbase	in (mm)	102.3 (2600)		108.3 (2750)		111 (2820)		
Height Over Cab with Standard Wheels	in (mm)	117.1 (2975)		118.9 (3020)		121.1 (3075)		
Overall Length with Front Weights	in (mm)	200 (5070)		207 (5260)		211 (5360)		
Base Weight without Ballast	lb (kg)	12,680 (5750)		14,440 (6550)		16,200 (7350)		

* Manufacturer's calculated estimate. ** With PowerPlus feature (boost). Boosted power is available only when certain operating conditions are met.

MCCORMICK

Tractor Model

Configurations Available

Performance

Rated ISO Engine HP @ 2200 RPM

Rated ISO PTO HP @ 2200 RPM*

Max. ISO Engine HP @ 1900 RPM

Max. ISO PTO HP @ 1900 RPM*

Max. Engine Torque @ 1400 RPM

Torque Rise

Engine

Engine Type

Engine Size

Fuel / DEF Capacity

Drive Train

Transmission Type

Ranges and Operating Modes

Rear Axle

Differential Lock

4wd Front Axle

Hydraulics, 3-point Hitch

Implement Hydraulic System Type /

Rear Remote Valves

Rear 3-point Hitch Type / Lift Capa

Rear PTO

Operator's Area

Cab

Seat and Front Dash

Integrated Display

Wheelbase

Height Over Cab with standard whe

Overall Length with front suitcase w

Base Weight without ballast

* Manufacturer's calculated estimate.

X7 Models with VT-Drive Transmission

X7.670	X7.680
Premium only	Premium only
166 (122)	181 (133)
140 (103)	150 (110)
192 (141)**	212 (156)**
157 (117)**	181 (135)**
597 (810)**	639 (867)**
41%	37%
ER) technology	
er	
3)	
n (50 kph) capable	
ptors	
agement	
raking; available suspension	
123)	
4 standard; up to 5 available	
Category 3; electronic control	
20,500 (9300)	
der controls	
available suspension	
ont dash with user interface	
111 (2820)	
121.1 (3075)	
211 (5360)	
16,200 (7350)	

Tractor Model		X7.450	X7.670
Configurations Available		Premium only	Premium only
Performance			
Rated ISO Engine HP @ 2200 RPM	HP (kW)	140 (104)	175 (129)
Rated ISO PTO HP @ 2200 RPM*	HP (kW)	110 (82)	145 (108)
Max. ISO Engine HP @ 1900 RPM	HP (kW)	150 (110) / 160 (118) with PowerPlus**	180 (133) / 194 (143) with PowerPlus**
Max. ISO PTO HP @ 1900 RPM*	HP (kW)	120 (89) / 130 (97) with PowerPlus**	150 (112) / 164 (122) with PowerPlus**
Max. Engine Torque @ 1400 RPM	lb ft (Nm)	494 (671)	597 (810)
Torque Rise		41 %	34 %
Engine			
Engine Type		BETAPOWER diesel engine; Tier 4 using advanced Selective Catalytic Reduction (SCR) technology	
Engine Size		4.5 Liter, 4-cylinder	6.7 Liter, 6-cylinder
Fuel / DEF Capacity	gal (liter)	74 (280) / 10 (38)	85 (320) / 10 (38)
Drive Train			
Transmission Type		'VT-Drive' continuously variable transmission (CVT) with infinite speeds and seamless acceleration; 32 mph (50 kph) capable	
Ranges and Operating Modes		4 adjustable virtual operating ranges (creeper, field, work, transport); 3 operating models (Auto, Manual, PTO); cruise control	
Rear Axle		Internal planetary final drives; wet disc brakes; flange axle with bar axle adaptors	
Differential Lock		Front and rear fully locking differentials; electronic control; hydraulic engagement	
4wd Front Axle		Push button engagement, center locking differential; outboard planetary final drives; 4-wheel braking; available suspension	
Hydraulics, 3-point Hitch, PTO			
Implement Hydraulic System Type / Flow	gpm (lpm)	Closed center PFC with dedicated pump / 32.5 (123)	
Rear Remote Valves		3 standard; up to 5 available	4 standard; up to 5 available
Rear 3-point Hitch Type / Lift Capacity @ Hitch	lb (kg)	Category 3; electronic control; rear fender controls / 20,500 (9300)	
Rear PTO		540 / 540E / 1000 / 1000E standard; electro-hydraulic engagement; rear fender controls	
Operator's Area			
Cab		Large 4-post structure; 2 doors; flat foot deck; high capacity auto HVAC; roofline window, available suspension	
Seat and Front Dash		Deluxe air suspended seat; tilt and telescopic steering wheel; hide-away instructor's seat; front dash with user interface	
Integrated Display		12 inch (305 mm) touch screen color display; ISO 11783 (ISOBUS) compliant with rear connector	
Wheelbase	in (mm)	102.3 (2600)	111 (2820)
Height Over Cab with standard wheel equipment	in (mm)	117.1 (2975)	121.1 (3075)
Overall Length with front suitcase weights	in (mm)	200 (5070)	211 (5360)
Base Weight without ballast	lb (kg)	15,101 (6850)	16,200 (7360)

* Manufacturer's calculated estimate. ** With PowerPlus feature (boost). Boosted power is available only when certain operating conditions are met.

X7 SERIES