

# Case 1840 Skid Loader

Purchased June 1992

Date	Hours	Oil Weight	Oil	Fuel	Air	Hyd	Greased	
7/12/93	80	Delvac 15/40	yes	no	no	no	yes	
10/21/96	181	Delvac 15/40	yes	yes	no	no	yes	
2/17/00	291	Delvac 15/40	yes	no	no	no	yes	
3/25/05	413	Delvac 15/40	yes	yes	pri.	No	yes	
11/8/08	513	Delvac 15/40	yes	no	pri.	No	yes	
12/23/09	552						yes	
12/22/10	627	Delvac 15/40	yes	no	pri	no	yes	
1/14/13	742	Delvac 15/40	yes	yes	pri	no	yes	
9/15/14	840	Put new 10 ply tires on from Farmers Union Oil						
11/24/15	857	Delvac 15/40	yes	no	no	no	yes	
11/24/15		Put new starter switch on						
8/7/16	980	Delvac 15/40	yes	no	no	no	yes	
8/16/16	998	Replaced water pump and had a 151 point inspection, and a serpentine belt						
		At titan machinery in pierre						
7/19/19	1093	Delvac 15/40	yes	no	pri	no	yes	
7/19/19		Put on a new cutting edge						
11/5/20		Put new starter switch on						
3/9/22		Put new battery in it						
3/10/22	1226	Delvac 15/40	yes	no	blowed	no	yes	
3/7/24	1326	Delvac 15/40	yes	no	blowed	no	yes	

**Case 1840 Uni-Loader**

Oil	Case J908616	Wix 51602	Napa 1602	Pur. L34421
Fuel	J903202	33472	Napa 3472	
P Air	A173290	42518	Napa 2518	
S Air	A173291	42519	Napa 2519	
Hyd.	D126922	51485	Napa 1485	

Oil & Filter Change Takes 11 Quarts or 2 3/4 Gallons of Oil

Hydraulic & Filter Takes 6 1/4 Gallons of Oil

Chain Compartments Takes 6 Quarts Per Side

Radiator Holds 4 1/2 Gallons

Mix Case HTO additive to SAE 10/30W engine oil for hydraulic system

Changing the hydraulic oil use 1.5 US quarts HTO additive to 6 1/4 gallons of oil

Adding to the hydraulic system mix 1 US quart of HTO additive to 5 gallons of oil

(20 to 1 ratio)