



# 1999 Ford Super Duty F-550 Reg Cab 141" WB XL

VIN: 1FDAF56F9XEE52839

Print

Like 8

Share

Post

- Summary
- Style & Trim
- Equipment
- Colors
- Tech Specs

Narrow Down By Style Reg Cab 141" WB XL ▼

## Tech Specs

Vehicle Name	Ford Super Duty F-550
Body Style	Reg Cab
Body Code	141" WB
Drivetrain	Rear Wheel Drive
Passenger Capacity	2, 3 2.0 min 3.0 max
Gross Axle Wt Rating - Front	6000 lbs 5600.0 min 6000.0 max
Gross Axle Wt Rating - Rear	13,500 lbs
Curb Weight - Front	3505 lbs 3505.0 min 3820.0 max
Curb Weight - Rear	2567 lbs 2550.0 min 2642.0 max
Gross Vehicle Weight Rating Cap	19,000, 17,500 lbs
Gross Combined Wt Rating	26,000 lbs
Dead Weight Hitch - Max Trailer Wt.	5,000 lbs
Dead Weight Hitch - Max Tongue Wt.	500 lbs 500.0 min 500.0 max
Wt Distributing Hitch - Max Trailer Wt.	10,000 lbs
Wt Distributing Hitch - Max Tongue Wt.	1,000 lbs
Fifth Wheel Hitch - Max Trailer Wt.	18,300 lbs
Engine Order Code	99F
Engine Type	Turbo Diesel V8
Displacement	7.3L/444



<b>Fuel System</b>	DI
<b>SAE Net Horsepower @ RPM</b>	235 @ 2700
<b>SAE Net Torque @ RPM</b>	500 @ 1600
<b>Trans Order Code</b>	446, 44E 446.0 min 446.0 max
<b>Trans Type</b>	6, 4 4.0 min 6.0 max
<b>Trans Description Cont.</b>	Manual w/OD, Automatic w/OD
<b>Trans Description Cont. Again</b>	Electronic
<b>First Gear Ratio (:1)</b>	5.79, 2.71 2.71 min 5.79 max
<b>Second Gear Ratio (:1)</b>	3.31, 1.54 1.54 min 3.31 max
<b>Third Gear Ratio (:1)</b>	2.10, 1.00 1.0 min 2.1 max
<b>Fourth Gear Ratio (:1)</b>	1.31, 0.71 0.71 min 1.31 max
<b>Fifth Gear Ratio (:1)</b>	1.00 1.0 min 1.0 max
<b>Sixth Gear Ratio (:1)</b>	0.72 0.72 min 0.72 max
<b>Reverse Ratio (:1)</b>	5.23, 2.18 2.18 min 5.23 max
<b>Clutch Size</b>	13.0 in 13.0 min 13.0 max
<b>Trans Power Take Off</b>	SAE 6-Bolt
<b>Trans PTO Access</b>	LH
<b>Cold Cranking Amps @ 0° F (Primary)</b>	750 650.0 min 750.0 max
<b>Cold Cranking Amps @ 0° F (2nd)</b>	750 750.0 min 750.0 max
<b>Maximum Alternator Capacity (amps)</b>	260, 130 95.0 min 260.0 max
<b>Maximum Alternator Watts</b>	3900, 1950 1425.0 min 3900.0 max
<b>Total Cooling System Capacity</b>	30.6 qts 28.5 min 30.6 max
<b>Frame Type</b>	Ladder
<b>Suspension Type - Front</b>	Multi-Leaf
<b>Suspension Type - Rear</b>	Multi-Leaf
<b>Spring Capacity - Front</b>	6000 lbs 5600.0 min 6000.0 max
<b>Spring Capacity - Rear</b>	13,500 lbs
<b>Axle Type - Front</b>	Monobeam

BigIron

<b>Axle Type - Rear</b>	Full-Floating
<b>Axle Capacity - Front</b>	6000 lbs 6000.0 min 6000.0 max
<b>Axle Capacity - Rear</b>	13,500 lbs
<b>Axle Ratio (:1) - Rear</b>	5.38, 4.88 4.88 min 5.38 max
<b>Shock Absorber Diameter - Front</b>	35.1 mm 35.1 min 35.1 max
<b>Shock Absorber Diameter - Rear</b>	35.1 mm 35.1 min 35.1 max
<b>Front Tire Order Code</b>	T9A, T91
<b>Rear Tire Order Code</b>	T9A, T91
<b>Spare Tire Order Code</b>	512, 515 512.0 min 515.0 max
<b>Front Tire Size</b>	225/70R19.5F
<b>Rear Tire Size</b>	225/70R19.5F
<b>Spare Tire Size</b>	225/70R19.5F
<b>Front Tire Capacity</b>	3640 lbs 3640.0 min 3640.0 max
<b>Rear Tire Capacity</b>	3415 lbs 3415.0 min 3415.0 max
<b>Spare Tire Capacity</b>	3640 lbs 3640.0 min 3640.0 max
<b>Revolutions/Mile @ 45 mph - Front</b>	653 Rev/Mile 653.0 min 653.0 max
<b>Revolutions/Mile @ 45 mph - Rear</b>	654, 653 Rev/Mile 653.0 min 654.0 max
<b>Revolutions/Mile @ 45 mph - Spare</b>	653, 654 Rev/Mile 653.0 min 654.0 max
<b>Front Wheel Size</b>	19.5 x 6.0 in
<b>Rear Wheel Size</b>	19.5 x 6.0 in
<b>Spare Wheel Size</b>	19.5 x 6.0 in
<b>Front Wheel Material</b>	Steel
<b>Rear Wheel Material</b>	Steel
<b>Spare Wheel Material</b>	Steel
<b>Steering Type</b>	Power
<b>Steering Ratio (:1), On Center</b>	20.3 20.3 min 20.3 max
<b>Turning Diameter - Curb to Curb</b>	51.98 ft 51.98 min 70.79 max
<b>Turning Diameter - Wall to Wall</b>	54.55 ft 54.55 min 73.39 max

<b>Brake Type</b>	Power
<b>Brake ABS System</b>	Four Wheel
<b>Disc - Front (Yes or )</b>	Yes
<b>Disc - Rear (Yes or )</b>	Yes
<b>Front Brake Rotor Diam x Thickness</b>	14.53 x 0.47 in
<b>Rear Brake Rotor Diam x Thickness</b>	15.55 x 0.47 in
<b>Fuel Tank Capacity, Approx</b>	19.0, 36.0 gal 19.0 min 36.0 max
<b>Fuel Tank Location</b>	Midship, Aft-of-Axle
<b>Front Head Room</b>	41.3 in 41.3 min 41.3 max
<b>Front Leg Room</b>	40.7 in 40.7 min 40.7 max
<b>Front Shoulder Room</b>	68.0 in 68.0 min 68.0 max
<b>Front Hip Room</b>	67.4 in 67.4 min 67.4 max
<b>Wheelbase</b>	140.8 in 140.8 min 200.8 max
<b>Length, Overall w/o rear bumper</b>	225.7 in 225.7 min 285.7 max
<b>Width, Max w/o mirrors</b>	93.6 in 93.6 min 93.6 max
<b>Height, Overall</b>	81.7 in 81.1 min 81.7 max
<b>Overhang, Front</b>	37.4 in 37.4 min 37.4 max
<b>Overhang, Rear w/o bumper</b>	47.5 in 47.5 min 47.5 max
<b>Front Bumper to Back of Cab</b>	118.2 in 118.2 min 118.2 max
<b>Cab to Axle</b>	60.0 in 60.0 min 120.0 max
<b>Cab to End of Frame</b>	107.5 in 107.5 min 167.5 max
<b>Ground to Top of Frame</b>	24.1 in 24.1 min 24.1 max
<b>Frame Width, Rear</b>	34.2 in 34.2 min 34.2 max
<b>Country of Origin</b>	United States Ford Incomplete Vehicle

« Colors

**Enter VIN**

1FDAF56F9XEE52839

BigIron