

DT(M)55 Series

Specifications & Capacities		
Model Numbers	DT55	DTM55
Horsepower Range	60-150 horsepower (45-112 kW)	
Hitch	Category 2 & Category 3, Quick-Hitch Adaptable	
Machine Weight (Without Options)	900 lbs (408 kg)	850 lbs (386 kg)
Tractor Power Take-Off	540 rpm	1000 rpm
Impeller rpm	740 rpm	730 rpm
Impeller	20" (51 cm) diameter	
Impeller Blades	6 ea., 3/8" (10 mm) thick steel with replaceable hardened cutting edges	
Chain	Double 80 chain with positive tension bolt	
Chaincase	Shell Gadus S2 V220 00 flowable grease or equivalent	
Lubrication type	119 oz.(3.52 L)	
Lubrication capacity		
Input/Output Shafts	2 1/4" ID ball type bearings	
Driveline	Cat. 5 with shear-bolt	
Material Control Chute (Optional)	Manual or with 2" X 8" hydraulic cylinder and hoses	
Depth Control Wheel (Optional)	16.5 X 6.50-8 pneumatic tire Adjustable from cutting edge to 10" below	
Ripper Shank (Optional)	3 height adjustments from cutting edge depth to 5" (13 cm) below Spring tine tip	
Skid Shoe (Optional)	3/8" (10 mm) thick, replaceable	

26765

