



LOWER GREAT LAKES - WHITEFORD - PERRYSBURG (L721)
 12650 ECKEL JUNCTION RD.
 PERRYSBURG, Ohio 43551

PALFINGER USA
 4151 WEST STATE ROUTE 18
 TIFFIN, Ohio 44883
 United States of America

Ron Lozier
 Cell Phone:
 Office Phone: 419-874-3511
 Email: rlozier@lglk.com

Vehicle Summary

	Unit	Chassis	
Model:	T880 Series Conventional	Fr Axle Load (lbs):	20000
Type:	FULL TRUCK	Rr Axle Load (lbs):	46000
Description 1:	ROOFING	G.C.W. (lbs):	80000
Description 2:	ECO of Chassis 374413 T880 Series Conventional		
	Application	Road Conditions:	
Intended Serv.:	Local pickup & delivery: Vehicles which	Class A (Highway)	90
Commodity:	General freight	Class B (Hwy/Mtn)	10
		Class C (Off-Hwy)	0
		Class D (Off-Road)	0
Type:	Body Flatbed with utility crane	Maximum Grade:	6
Length (ft):	20	Wheelbase (in):	250
Height (ft):	13.5	Overhang (in):	140
Max Laden Weight (lbs):	4000	Fr Axle to BOC (in):	74
		Cab to Axle (in):	176
		Cab to EOF (in):	316
		Overall Comb. Length (in):	438.5
		Special Req.	
		U.S. Domestic registry, 50-state.	
No. of Trailer Axles:	0		
Type:			
Length (ft):	0		
Height (ft):	0		
Kingpin Inset (in):	0		
Corner Radius (in):	0		
	Restrictions		
Length (ft):	120		
Width (in):	102		
Height (ft):	13.5		

Approved by: _____

Date: _____

Note: All sales are F.O.B. designated plant of manufacture.

Std/ Opt	Description	Weight
Model		
S	T880 Series Conventional	15,549
S	T880	0
O	CARB Idle Emissions Reduction - MX	0
S	Non-Sleeper w/rear axle capacity less than 59K.	0
O	State of Registry: Ohio	0
Engine & Equipment		
O	MX-13 485 485@1600 1650@900 N09020 AE001 NO....ENBL MX RETARDER IN NEUTRAL N08200 AE002 650...IDLE TARGET N09100 AA003 68....CC MAX TARGET SPD N09110 AA004 16....CC MIN ENABLE SPD N09120 AA005 OFF...DYNAMIC CC ENABLE N09440 AA061 2000..CAB:MAX ENG SPD-ACCEL CNTRL N09430 AA062 2000..CAB: MAX ENG SPD - SW CNTRL N09420 AA063 6.....CAB: MAX VEH SPD N09510 AA065 800...CAB: DEDICATED PRESET "-" N09520 AA066 900...CAB: DEDICATED PRESET "+" N09780 AA049 CNCL..CAB: CUSTOM PRESET 1 FUNC N09640 AA050 750...CAB: CUSTOM PRESET 1 N09790 AA051 CNCL..CAB: CUSTOM PRESET 2 FUNC N09650 AA052 850...CAB: CUSTOM PRESET 2 N09800 AA053 CNCL..CAB: CUSTOM PRESET 3 FUNC N09660 AA054 950...CAB: CUSTOM PRESET 3 N09500 AA060 OFF...CAB: PRESET +/- SW TYPE N09630 AA067 TRQ...CAB:ACCEL PEDAL TYPE IN PTO N09400 AA068 YES...CAB:ACCEL ACTV IN CAB PTO N09470 AA055 OFF...CAB: CLUTCH INTLK N09840 AA056 OFF...CAB: CUSTOMER INTLK N09480 AA057 ON....CAB: NEUTRAL INTLK N09460 AA058 ON....CAB: PARK BRK INTLK N09490 AA059 ON....CAB:SER BRK INTLK:NO PTO N09540 AA074 2000..REM:MAX ENG SPD-ACCEL CNTRL N09530 AA075 2000..REM:MAX ENGSPD-SW/TSC1 CTRL N09610 AA077 1200..REM: DEDICATED PRESET "-" N09620 AA078 1200..REM: DEDICATED PRESET "+" N09810 AA043 CNCL..CAB/REM:CUSTOM PRESET1 FUNC N09670 AA044 750...CAB/REM: CUSTOM PRESET 1 N09820 AA045 CNCL..CAB/REM:CUSTOM PRESET2 FUNC N09680 AA046 850...CAB/REM:CUSTOM PRESET 2 N09830 AA047 CNCL..CAB/REM:CUSTOM PRESET3 FUNC N09690 AA048 950...CAB/REM: CUSTOM PRESET 3 N09600 AA079 OFF...REM: PRESET +/- SW TYPE N09410 AA069 YES...PTO REM PEDAL ENABLE N09560 AA070 OFF...REM: CLUTCH INTLK	0

Std/ Opt	Description	Weight
	N09700 AA071 OFF...REM: CUSTOMER INTLK	
	N09570 AA072 OFF...REM: NEUTRAL INTLK	
	N09580 AA073 OFF...REM:SER BRK INTLK:NO PTO	
	N09550 AA076 650...REM: MIN ENG SPD	
	N09450 AA064 650...CAB: MIN ENG SPD	
	N09760 AA009 5.....DRIVER REWARD VEH SPD BONUS	
	N09770 AA010 -5.....DRIVER REWARD VEH SPD PNLTY	
	N09750 AA013 NONE..OFFSET MODE	
	N09720 AA015 3.....MIN SPD FOR DR SHIFT AID	
	N09730 AA016 1.....DSA LOWEST ACTV GEAR	
	N09740 AA017 6.....DSA HIGHEST ACTV GEAR	
	N09340 AA019 YES...EIST PARK BRK RESET ENABLE	
	N09300 AA022 30....EIST LO CLNT TEMP OVERRIDE	
	N09290 AA023 80....EIST HI AMBAIR TEMP OVRRDE	
	N09280 AA024 40....EIST LO AMBAIR TEMP OVRRDE	
	N09260 AA025 5.....EIST PTO MAX IDLE TIME	
	N09230 AA026 5.....EIST PARKED MAX IDLE TIME	
	N09220 AA027 5.....EIST STANDSTILL IDLE TIME	
	N09240 AA029 YES...EIST RESET FROM ENG LOAD	
	N09250 AA030 NO....EIST OVERRIDE FROM ENG LOAD	
	N09200 AA031 0.....EIST EXPIRATION DISTANCE	
	N09310 AA032 YES...EIST ACCEL PEDAL RESET	
	N09330 AA033 YES...EIST SERVICE BRK RESET	
	N09320 AA034 YES...EIST CLUTCH PEDAL RESET	
	N09270 AA035 YES...EIST PTO OVERRIDE	
	N08030 AA086 68....MAX ACCEL PEDAL VEH SPD	
	N08000 AA087 0.....VSL EXPIRATION DISTANCE	
	N08020 AA088 100...LRSL SPD LMT	
	N09350 AA042 1900..FAST IDLE CNTRL MAX ENG SPD	
	N09050 AA037 4.....DSL SPD OFFSET	
	N09040 AA038 2.....AUTO RTRDR VEH SPD OFFSET	
	N09030 AA039 0.....TIME DELAY FOR RTRDR ACT	
	N09130 AA006 MT....MULTI TORQUE IN CC	
	N09080 AQ001 4.....PCC Negative Offset	
	N09090 AQ002 4.....PCC Positive Offset	
	N09710 AA089 NO....REMOTE INPUTS IN CAB PTO	
	N08200 AE002 650...IDLE TARGET	
O	EPA Emissions Warranty Engine	0
S	PremierSpec	0
O	Engine monitoring protection -Derate- PACCAR MX	0
O	Gearing Analysis: Performance	0
O	Customer's Typical Operating Spd: 68 mph.	0
O	MX Retarder State Cruise Control On Latch Mode	0
O	Enable MX Retarder Auto-Retard	0

<i>Std/ Opt</i>	<i>Description</i>	<i>Weight</i>
O	Enable MX Retarder Downhill Speed Limiter	0
O	PTO mode control - remote station.	0
O	Effective VSL Setting NA	0
O	Engine Idle Shutdown Timer Disabled	0
O	Enable EIST Ambient Temp Overrule	0
O	Eff EIST NA Expiration Miles	0
S	Air Compressor: WABCO 25.9 CFM PACCAR MX	0
S	Air Cleaner: composite firewall mounted PACCAR or	0
S	Fan hub: Horton 2-Speed for PACCAR MX	0
S	Cooling module: 1330 square inches.	0
S	EXH: 2021 RH Under DPF/SCR with RH SOC Vertical	0
O	Tailpipe: 5 in. single 30 in. 45 degree curved.	-1
S	Fuel Filter: PACCAR Extended Service Interval	0
S	Run Aid:Fuel Heat	0
S	Start Aid:12V Heat	0
O	Immersion block heater 120V 1500W w/plug under	2
S	Alternator: PACCAR HDS 160 AMP Brushed	0
S	Batteries: 3 PACCAR GP31 threaded post (700-730)	0
S	PACCAR Premium 12V Starter with PACCAR MX Engines	0
S	12V low voltage disconnect for starter battery	0
O	Remote PTO/Throttle, 12-Pin, 250K End of Frame,	0
O	Remote Presets and Interlock, 8-Pin, End of Frame	0
Transmission & Clutch		
O	Transmission: Allison 4500RDS 6-speed, With PTO	478
O	Driveline: 3 Dana 1810 heavy-duty W/2	160

<i>Std/ Opt</i>	<i>Description</i>	<i>Weight</i>
O	Torque converter included w/Allison	0
O	Pushbutton control center console mounted.	0
O	Allison Fuel Sense: Delete	0
O	J1939 Park Brake Auto Neutral	0
U	Decline Allison Neutral at Stop Stand-Alone	0
O	Customer installed transmission PTO in the LH	0

Front Axle & Equipment

S	PACCAR FX-20 Front Axle rated at 20K 4" drop	0
O	Front Brakes: 22K Bendix ES S-cam 16.5x6 in.	-46
O	Front Brake Drum: 22,000 lbs. 16-1/2x6 in. Cast.	104
O	Front Hubs Iron hub pilot 20,000 lbs. 10 Bolt	80
S	ConMet PreSet Plus Hub package; front axle.	0
S	Hubcap: front vented.	0
O	Front Auto Slack Adjuster.	0
S	Front Springs: Taperleaf 20K w/ shock absorbers	0
S	Dual power steering gear: 16-22K Sheppard HD94.	0
S	Power Steering Cooler:Radiator Mounted Air-to-Oil	0
O	Front Frame Raised: 1/2 in.	0

Rear Axle & Equipment

S	Dual Meritor RT46-160 rear axle rated at 46K.	0
O	Rear Axle Ratio - 4.30.	0
S	Dual Rear Brakes 16-1/2x7 in. to 46K;	0
S	Dual Rear Brake Drums: cast.	0
S	Dual Rear Hubs: Aluminum hub pilot 46K	0
S	ConMet PreSet Plus Hub package; dual rear axle.	0

<i>Std/ Opt</i>	<i>Description</i>	<i>Weight</i>
S	Dual Rear axle automatic slack adjusters.	0
S	Spring Brake: 3030 long stroke dual 30 square	0
O	Bendix 6S/6M anti-lock brake system.	5
O	Interaxle driveline:1 Dana 1710 Series	-12
O	Driver Controlled Differential Lock (Crosslock)	39
O	Rear suspension: Tandem Hendrickson Primaax EX462	202
O	1 Steerable Tag Watson-Chalin 13.5K SL13	1,245
O	1 Steerable Tag Brakes: Bendix Non-RSD15X4	0
O	1 Steerable Tag cast drum 15x4 for use with	0
O	1 Steerable tag hubs aluminum hub pilot 10-bolt	0
O	Locking tag kit: required w/ multiple axles.	30
O	Pusher or Tag: gauge/ switch dash-mounted, gauge	0
O	Delete standard heavy-duty air springs for rear	-28
O	Tag location: 65 in. from c/l of rearmost axle or	0
Tires & Wheels		
S	Front tires: Goodyear Armormax MSA 425/65R22.5	-8
O	Rear tires: Continental HDR2+ 11R22.5 14PR	176
O	1 Steerable Tag: 2 Goodyear Endurance RSA	-40
O	Rear Tire Quantity: 8	0
O	Front Wheel: Alcoa 82362 22.5x12.25 aluminum,	-10
O	Rear Wheel: Alcoa ULA18/Accuride 51487	-208
O	1 Steerable Tag Wheel: 2 Alcoa ULA18 22.5x8.25	-51
O	Powder coat white steel wheel. Use in conjunction	0
O	Single Front Axle Wheels: Dura-Bright Mirror	0
O	Rear Wheel/Rim Quantity: 8	0

Std/ Opt	Description	Weight
Frame & Equipment		
O	Frame Rails: 10-3/4 x 3-1/2 x 3/8in. Steel 417in.	734
O	Full Steel Insert: for 10-5/8 in. or 10-3/4 in.	843
O	Bumper: Tapered chrome steel channel. Requires a	63
S	48.5 in. Bumper setting. Requires a bumper code.	0
O	Front tow hook: Center mounted, cast.	28
U	CUSTOM FRAME LAYOUT: FLEET MGMT ONLY CFL A/T: A/TS CANNOT EXTEND ABOVE TOP OF FRAME RAILS, NO A/TKS IN TRANSMISSIN AREA CFL DEF: MOUNT DEF TANK AS CLOSE TO FUEL TANK AS POSSIBLE SAME	0
O	Battery box cantilever aluminum BOC with	8
O	Battery box location: RH Side.	15
S	T470,C5, T6, T8 non-polished DPF/SCR or CNG cover	0
O	First - RH outside and RH below rail only.	0
O	Second - LH outside and LH below rail only.	0
O	Directly behind BOC1 fuel/hydraulic tank or box.	0
O	Directly behind DEF tank.	0
O	First - 60 in. clear frame space length.	0
O	Second - 60 in. clear frame space length.	0
O	Width across front tires exceeds 102 inches.	0
O	Chassis too long for delivery in standard 3 way	0
S	Rear mudflap arms: Betts B-25 standard-duty,	0
S	Rear mudflap shields: White plastic antisail w/	0
S	Square end-of-frame w/o crossmember; non-towing.	0
Fuel Tanks & Equip		
O	Fuel Tank: 100 US gallon 24.5in. aluminum under	0

<i>Std/ Opt</i>	<i>Description</i>	<i>Weight</i>
S	Small round DEF tank, 14 gallons.	0
O	Fuel Tank Steps: 6in. wide upper & lower F/1 LH	8
S	DEF to fuel fill ratio 2:1 or greater.	0
S	Anti-siphon device in fuel tank filler neck.	0
S	DEF tank location is LH.	0
O	Location: 100 gal fuel tank LH under cab	0

Cab & Equipment

S	Cab: Stamped aluminum cab with panoramic curved	0
O	Hood: T880 Standard Length With Mechanically	15
O	Bright Engine Air Intake	0
S	Cab HVAC - Day Cab and 40in Sleeper	0
S	Kenworth Smartwheel: 18 in. Non-Leather With	0
O	Column Mtd Retarder Control, RH Side	0
S	Adjustable telescoping tilt steering column.	0
O	5 sets of keys. Replaces standard 2 sets of keys.	0
O	Dash Mounted Compact Trailer Brake Valve.	0
O	Dash Switch: 1st Allison-mntd PTO.	0
U	Info for C/I PTO: Chelsea 10 Bolt	0
O	Four Spare Switches: Wired To Power.	0
O	Gauge: Air suspension pressure gauge.	0
O	Gauge: Engine Oil Temperature Gauge With Integral	0
S	Gauge: DD Virtual Gauge - Oil Temp Engine	0
S	Gauge: DD Virtual Gauge - Air Filter	0
S	Gauge: DD Virtual Gauge - Manifold	0
S	Gauge: DD Virtual Gauge - Engine Percent	0

<i>Std/ Opt</i>	<i>Description</i>	<i>Weight</i>
S	Main Instrument Package: 15" Digital Display.	0
O	USB Charging Port - Dash Panel	0
S	Interior color: Slate Gray	0
S	Interior package: Vantage daycab	0
S	Rubber floormat	0
S	Driver Seat: GT701 HB with DuraCloth w/ Vinyl	0
S	Rider Seat: GT100 Toolbox HB with DuraCloth w/	0
S	Seat Color: Black	0
O	Kenworth Radio DEA710 AM/FM/WB/USB, Bluetooth	0
S	Base Level Audio System - Daycab:High Performance	0
O	CB installation kit: Center mounted of header.	2
S	Turn Signal: Non-Self Cancelling	0
S	LH and RH Trip Ledge Rain Deflectors	0
S	Kenworth TruckTech+	0
O	Long grabhandle RH side mounted to side-of-cab	2
O	Grabhandle: LH, Exterior, Side of Cab - Ergonomic	3
S	Dual Cab Interior Grabhandles: A Pillar Mounted	0
S	Kenworth Daylite Door with standard LH/RH	0
S	Single air horn under cab.	0
S	Look-Down, Pass. Door, Black 11x6	0
O	Mirror: LH Hood Mounted, Round Convex, Chrome	4
O	Mirror: RH Hood Mounted, Round Convex, Chrome	4
S	Aero Mirror: Dual Kenworth Aerodynamic Motorized	0
S	Rear cab stationary window 19in x 36in	0
S	One-piece bonded-in windshield with curved glass.	0

<i>Std/ Opt</i>	<i>Description</i>	<i>Weight</i>
S	Exterior stainless steel sunvisor.	19
O	Fender close-out: Below headlamp, behind	0
O	Wheelwell Fender Extension: 4.5 inches	1
S	Kenworth Cab/Sleeper Air Suspension.	0

Lights & Instruments

S	Headlamps: SAE Dual Halogen Complex Reflector	0
S	Marker Lights: Five, rectangular, LED	0
S	Turn Signal Lights: Flush mounted LED. Mounted at	0
S	LED Stop,Turn,Tail: With Two LED	0
O	SW/WIRE/IND LT: C/I FLOOD 1ST SW THRU	0
S	Marker Lights: Interrupter Switch.	0
S	Omit Brake Light with Engine Brake.	0
O	Reflectors: Two Midframe	0
O	Electric Backup Alarm: Meets SAE J994 & OSHA	4
O	Polyswitches replacing fuses. Switch will	0

Air Equipment

S	Air Dryer: Bendix AD-HF Puraguard Heated	0
S	Moisture ejection valve w/ pull cable drain.	0
O	Full Truck Kit	15
S	Nylon air tubing in frame & cab, excluding hoses	0
O	Bendix LQ-5 ratio valve:for Kenworth-installed	2
O	Locate air dryer inside RH rail BOC.	0
O	Air tanks: mounted inside frame flanges	0
O	Trailer ABS electric supply through SAE J560	0

Extended Warranty

Std/ Opt	Description	Weight
O	Base Warranty - PACCAR MX-11 & MX-13 Engine	0
S	Base Warranty - Standard Service Heavy Duty	0
U	HD TECHNOLOGY FEE	0
	<i>Narr HD TECHNOLOGY FEE</i>	
S	24 Month TruckTech+ Subscription for PACCAR MX	0
O	Base Warranty: Emissions	0
Miscellaneous		
U	2023 FREIGHT SURCHARGE	0
	<i>Narr 2023 FREIGHT SURCHARGE</i>	
O	GHG Secondary Manufacturer: Does Not Apply	0
O	Additional lead time required for off highway &	0
O	Warning triangle reflector kit: Shipped loose.	4
S	VMUX Architecture	0
Promotions		
U	SPEC INVS - MX13 ENGINE ONLY >= 1/1/20	0
	<i>Narr SPEC INVS - MX13 ENGINE ONLY >= 1/1/20</i>	
U	2023 SCHEDULING CODE - FLEET	0
	<i>Narr 2023 SCHEDULING CODE - FLEET</i>	
U	2023 2ND HALF 2023 FCA - HD	0
	<i>Narr 2023 2ND HALF 2023 FCA - HD</i>	
Paint		
O	Paint color number(s). N9702 A - L0006 WHITE N9720 FRAME N0001 BLACK	0
O	Bumper Unpainted	0
O	Day Cab Bulk Paint	0
O	Day Cab Standard Paint	0
S	1 - Color Paint - Day Cab	0
S	Base coat/clear coat.	0

<i>Std/ Opt</i>	<i>Description</i>	<i>Weight</i>
0	Cancel/reorder chassis.	0
<i>Narr 275631, 275632, 275633, 275667</i>		

Order Comments

Total Weight

19,440

Prices and Specifications Subject to Change Without Notice.

Unpublished options may require review/approval.

Dimensional and performance data for unpublished options may vary from that displayed in CRM.

PRICING DISCLAIMER

While we make every effort to maintain the web site to preserve pricing accuracy, prices are subject to change without notice. Although the information in this price list is presented in good faith and believed to be correct at the time of printing, we make no representations or warranties as to the completeness or accuracy of this information. We reserve the right to change, delete or otherwise modify the pricing information which is represented herein without any prior notice. We carefully check pricing specifications, but occasionally errors can occur, therefore we reserve the right to change such prices without notice. We disclaim all liability for any errors or omissions in the materials. In no event will we be responsible for any damages of any nature whatsoever from the reliance upon information from these materials. Please check your order prebills to confirm your pricing information



Shipping Destinations

Intermediate Destination: NONE

Final Destinations	Quantity	Beginning Chassis	Ending Chassis
L721 - LOWER GREAT LAKES - WHITEFORD - PERRYSBURG 12650 ECKEL JUNCTION RD. PERRYSBURG, Ohio 43551	4	374413	374416