

RTV

RTV1140

SPECIFICATIONS

Specifications

Model		RTV1140CPX Orange	RTV1140CPX RealTree®* Camouflage
Engine	Make	KUBOTA D1105-E3-UV	
	Type	3-cylinders, Water cooled 4-cycle, diesel, OHV	
	Displacement	cu.in (cc)	68.5 (1123)
	Horsepower	HP (kW)/rpm	24.8 (18.5)@3000
Fuel tank capacity	U.S.gals (ℓ)	7.9 (30)	
Transmission		Variable hydro transmission (VHT)	
Max. Traveling speed	mph (km/h)	25 (40)	
Wheels, drive system		Rear 2WD or 4WD selection	
Differential lock		Standard; foot operated with mechanical holder	
Gear selection		Hi-Med-Lo range forward, neutral, reverse	
Brakes	Front / Rear	Wet-disc brake	
	Parking brake	Rear wheel, hand lever	
Steering		Hydrostatic power	
Suspension	Front / Rear	Independent, Mac-Pherson strut-type / Semi-independent, DeDion axle w/leaf springs and shock absorbers	
Dimensions	Length	in. (mm)	137.0 (3480)
	Width	in. (mm)	61.0 (1550)
	Height, overall	in. (mm)	78.7 (2000)
	Front tread centers	in. (mm)	45.3 (1150)
	Rear tread centers	in. (mm)	46.5 (1180)
	Wheelbase	in. (mm)	95.1 (2415)
	Ground clearance front/rear axle	in. (mm)	8.3 (210) / 7.5 (190)
	Turning diameter	ft. (m)	32.8 (10)
Max. rolling weight (Towing capacity)	lbs. (kg)	1300 (590)	
Payload capacity	lbs. (kg)	1609 (730)	
Weight	lbs. (kg)	2392 (1085)	
Cargo bed	Width × Length × Depth	in. (mm)	1ROW:52.0(1320)×53.5(1360)×11.4(290) 2ROWS:52.0(1320)×33.9(860)×11.4(290)
	Volume	cu ft. (m ³)	1ROW:18.7(0.53) 2ROWS:11.7(0.33)
	Bed height (unloaded)	in. (mm)	33.5 (850)
	Cargo bed load	lbs. (kg)	1ROW:1102(500) 2ROWS:661(300)
Tires	Front		25×10-12 ATV, 6PLY
			25×10-12 HDWS, 6PLY
		25×12-12 TURF, 4PLY	—
	Rear		25×11-12 ATV, 6PLY
			25×10-12 HDWS, 6PLY
		25×12-12 TURF, 4PLY	—
Front guard		Std.	
Hydraulic bed lift		Std.	
Speedometer		Std.	

*RealTree® is a registered trademark of Jordan Outdoor Enterprises, Ltd.
The company reserves the right to change the above specifications without notice. This brochure is for descriptive purposes only. Please contact your local Kubota dealer for warranty and safety information.
The values in "Ground clearance" and "Weight" are those of the machine equipped with the tires. Some RTVs in this web site are shown with optional accessories. For off-highway use only.