

SSV Series

Specifications

SSV65



Model		SSV65	
Type of operator station		Open CAB / Closed CAB	
Engine	Model	V2607-CR-TE4	
	Emission certification	Tier 4	
	Gross HP (SAE J1995)	HP (kW)/rpm	64.0 (47.7) / 2700
	Net HP (SAE J1349)	HP (kW)/rpm	61.3 (45.7) / 2700
	Peak Torque @1500 rpm	lbf-ft (Nm)	166 (225)
	Displacement	cu.in. (cc)	159.7 (2615)
	Cylinders		4
	Bore Stroke	in.(mm)	3.5 (87) × 4.4 (110)
	Aspiration		Turbocharged
Loader performance	Rated operating capacity-50% tipping load	lbs. (kg)	1950 (885)
	Tipping load	lbs. (kg)	3900 (1770)
	Breakout force	Bucket	4839 (2195)
		Lift arm	3858 (1750)
	Lift arm path		Vertical
Power train	Standard tire size	ft.in. (mm)	10-16.5-8PR
	Chain size ASA#	ft.in. (mm)	80
	Travel speed	Low	6.9 (11.1)
		High	11.1 (17.8)
	Traction force	lbf. (kgf)	7339 (3329)
	Ground clearance	in. (mm)	7.6 (193)
Hydraulic system	Loader hydraulic flow	gpm (/min.)	18.0 (68.0)
	Loader hydraulic pressure	psi (kgf/cm2)	3271 (230)
	Aux. hydraulic flow	Standard	18.0 (68.0)
		High	28.0 (106.0)
Service refill capacities	Hydraulic tank	gal. ()	4.2 (16.0)
	Fuel tank	gal. ()	25.4 (96.0)
Operating weight (Include operator weight 175 lbs.)		lbs. (kg)	6790 (3080) / 7055 (3200)

Note: The above dimensions are based on the machine with std. tires, skid steer type quick coupler, standard bucket and ROPS/FOPS canopy and cabin. The company reserves the right to change the above specifications without notice. This brochure is for descriptive purposes only. Please contact your local Kubota dealer for warranty information. For your safety, Kubota strongly recommends the use of a Rollover Protective structure (ROPS) and seat belt in almost all applications.

SSV Series

Specifications

SSV75



Model			SSV75
Type of operator station			Open CAB / Closed CAB
Engine	Model		V3307-CR-TE4
	Emission certification		Tier 4
	Gross HP (SAE J1995)	HP (kW)/rpm	74.3 (55.4) / 2600
	Net HP (SAE J1349)	HP (kW)/rpm	71.6 (53.4) / 2600
	Peak Torque @1500 rpm	lbf-ft (Nm)	196 (265)
	Displacement	cu.in. (cc)	203.3 (3331)
	Cylinders		4
	Bore Stroke	in.(mm)	3.8 (94) × 4.8 (120)
	Aspiration		Turbocharged
Loader performance	Rated operating capacity-50% tipping load		lbs. (kg)
	Tipping load		5380 (2440)
	Breakout force	Bucket	lbf. (kgf)
		Lift arm	5884 (2669)
	Lift arm path		4850 (2200)
			Vertical
Power train	Standard tire size		ft.in. (mm)
	Chain size ASA#		12-16.5-10PR
	Travel speed	Low	ft.in. (mm)
		High	100
	Traction force	Low	mph (km/h)
		High	7.4 (11.9)
	Ground clearance		11.8 (19.0)
			8494 (3853)
			8.1 (207)
Hydraulic system	Loader hydraulic flow		gpm (/min.)
	Loader hydraulic pressure		20.9 (79.0)
	Aux. hydraulic flow	Standard	psi (kgf/cm2)
		High	3271 (230)
			20.9 (79.0)
			30.4 (115.0)
Service refill capacities	Hydraulic tank		gal. ()
	Fuel tank		4.2 (16.0)
			26.9 (102.0)
Operating weight (Include operator weight 175 lbs.)		lbs. (kg)	8157 (3700) / 8422 (3820)

Note: The above dimensions are based on the machine with std. tires, skid steer type quick coupler, standard bucket and ROPS/FOPS canopy and cabin. The company reserves the right to change the above specifications without notice. This brochure is for descriptive purposes only. Please contact your local Kubota dealer for warranty information. For your safety, Kubota strongly recommends the use of a Rollover Protective structure (ROPS) and seat belt in almost all applications.