

Victor Leggett

WELL SPECIFICATIONS		PUMPING REQUIREMENTS		PUMP SPECIFICATIONS		
Driller	<u>Traut</u>	Pivot Pressure	PSI <u>35</u>	FEET <u>80</u>	Manufacturer	<u>Berkley</u>
Date	<u>2001</u>	Well Lift	<u> </u>	<u>69</u>	Date Installed	<u>2002</u>
Depth	<u>158'</u>	Elevation (pivot)	<u> </u>	<u>13</u>	Installed by	<u>MUE</u>
Casing	Diameter	Elevation (field)	<u> </u>	<u> </u>	Model	<u>8T40-725</u>
	Thickness	Mainline Loss	<u> </u>	<u> </u>	Serial #	<u> </u>
Screen	Length	Misc. Loss	<u> </u>	<u> </u>	No. of Stages	<u>1</u>
	Diameter	Other	<u> </u>	<u>8</u>	Impeller Trim	<u>Full</u>
	Material		<u> </u>	<u> </u>	Top & Bottom Dimensions	<u>6"</u>
	Type		<u> </u>	<u> </u>	Intermediate Dimensions	<u>6 x 21</u>
	Slot		<u> </u>	<u> </u>	Column No.	<u>100'</u>
Pumping Level	<u>69</u>	TDH TOTAL	<u> </u>	<u>170</u>	Tail Pipe	<u> </u>
Static Level	<u>60'</u>	Gallon/Minute	<u> </u>	<u>700</u>	Discharge Head	<u>6"</u>
Draw Down	<u>9</u>	Pump Efficiency %	<u> </u>	<u>75</u>	Lube Equipment	<u>water</u>
Specific Yield	<u> </u>	Brake HP requirements	<u> </u>	<u>40</u>	Power Unit Type	<u>Else</u>
Est. Capacity	<u> </u>				Serial #	<u> </u>
Tested at	<u>1200</u>				Manufacturer	<u>Franklin</u>
					Model	<u>WYE-Delta</u>
					Horsepower	<u>40</u>
					RPM	<u>3600</u>
					TOTAL DEPTH OF SETTING	<u>107</u>
Attach: Well record		TDH X GPM		Brake HP	Attach: Pump curve	
Pumping record		3960 X Pump eff. X Derate			Equipment Invoice	
Permit application						